Sponsor: Terry Jackson Bossong Medical 840 W. Salisbury St. Asheboro, NC 27203

Latex Particle Challenge Final Report

Test Article: 190

Purchase Order: 30699

Study Number: 1284798-S01

Study Received Date: 04 Apr 2020

Testing Facility: Nelson Laboratories, LLC

6280 S. Redwood Rd.

Salt Lake City, UT 84123 U.S.A.

Test Procedure(s): Standard Test Protocol (STP) Number: STP0005 Rev 07

Deviation(s): Quality Event (QE) Number(s):

QE22125

Summary: This procedure was performed to evaluate the non-viable particle filtration efficiency (PFE) of the test article. Monodispersed polystyrene latex spheres (PSL) were nebulized (atomized), dried, and passed through the test article. The particles that passed through the test article were enumerated using a laser particle counter.

A one-minute count was performed, with the test article in the system. A one-minute control count was performed, without a test article in the system, before and after each test article and the counts were averaged. Control counts were performed to determine the average number of particles delivered to the test article. The filtration efficiency was calculated using the number of particles penetrating the test article compared to the average of the control values.

The procedure employed the basic particle filtration method described in ASTM F2299, with some exceptions; notably the procedure incorporated a non-neutralized challenge. In real use, particles carry a charge, thus this challenge represents a more natural state. The non-neutralized aerosol is also specified in the FDA guidance document on surgical face masks. All test method acceptance criteria were met. Testing was performed in compliance with US FDA good manufacturing practice (GMP) regulations 21 CFR Parts 210, 211 and 820.

Test Side: Inside

Area Tested: 91.5 cm2

Particle Size: 0.1 µm

Laboratory Conditions:

21°C, 30% relative humidity (RH) at 1053; 22°C, 30% RH at 1308

Average Filtration Efficiency: 78%

Standard Deviation:





Study Director

801-290-7500

Curtis Gerow, B.S.

Z7 APR ZOZO Study Completion Date

1284798-S01

nelsonlabs.com

| sales@nelsonlabs.com

FRT0005-0001 Rev 6



Deviation Details: Controls and sample counts were conducted for one minute instead of an average of three one minute counts. This change shortens the total test time for each sample but will still provide an accurate determination of the particle counts. An equilibrate is a dwell period where the challenge is being applied to the test article for a certain period of time before test article counts are counted. The equilibrate period was reduced from 2 minutes to a minimum of 30 seconds which is sufficient time to clear the system of any residual particles, and establish a state of stable equilibrium before sample counts are taken. Test method acceptance criteria were met, results are valid.

Results:

Test Article Number	Test Article Counts	Average Control Counts	Filtration Efficiency (%)
1	2,365	10,627	78
2ª	1,670	11,957	86
	2,027	11,884	83
3	2,995	11,317	74
4	2,926	10,862	73
5	2,968	11,717	75

The original result for this test article was unexpected when compared to the other test articles. Investigational testing was performed on the same test article in duplicate and it was determined that the original result was invalid. Only the investigational test results are reported.